

ALUPROF – INFORMACJA

Średnice nawojowe dla profili roletowych

Średnice nawojowe dla profilu PA 37 [mm]		
wysokość	rura SW 40	rura SW 60
500	86	95
750	98	106
1000	113	118
1250	116	124
1500	125	130
1750	133	144
2000	141	145
2250	148	153
2500	155	158
2750	161	165
3000	167	171
3250	172	178
3500	179	184
3750	184	188
4000	191	193
4250	194	198
4500	201	204
4750	205	209
5000	210	213

Średnice nawojowe dla profilu PA 39 [mm]		
wysokość	rura SW 40	rura SW 60
500	87	96
750	99	106
1000	111	118
1250	116	124
1500	125	133
1750	133	142
2000	144	151
2250	152	156
2500	158	163
2750	164	171
3000	171	177
3250	178	184
3500	186	190
3750	192	197
4000	199	200
4250	206	206
4500	209	214
4750	213	219
5000	219	226

Średnice nawojowe dla profilu PA 45 [mm]	
wysokość	rura SW 60
500	110
750	115
1000	130
1250	138
1500	144
1750	155
2000	170
2250	177
2500	185
2750	190
3000	193
3250	199
3500	203
3750	204
4000	212
4250	217
4500	228

Średnice nawojowe dla profilu PA 52 [mm]	
wysokość	rura SW 60
500	108
750	120
1000	130
1250	140
1500	152
1750	161
2000	169
2250	178
2500	187
2750	197
3000	204
3250	210
3500	218
3750	225
4000	233

Średnice nawojowe dla profilu PA 55 [mm]	
wysokość	rura SW 60
500	115
750	131
1000	145
1250	161
1500	173
1750	185
2000	194
2250	202
2500	211
2750	219
3000	232
3250	240